


MV Halogen without Reflector EcoHalo Linear Compact



B	C	D
nom.	max.	max.
74.9	78.3	12

Product Description

- Mains-voltage, double-ended linear halogen lamp with energy-saving capabilities

Product Features

- Fully interchangeable with mains-voltage double-ended linear halogen lamps
- Constant light output during life.

Application

- Indoor: homes, offices, shops, museums
- Outdoor: billboards, car park security lighting.

Type	Wattage	Cap-Base	Voltage	Packing type	Packing configuration	Luminous flux lamp (lm)	Life to 50% failures (h)	Ordering number 8727900...
EcoHalo 78mm 2y	48W	R7s	230V	1BC	10	750	2000	920925 00
EcoHalo 78mm 2y	48W	R7s	230V	1BC	10	750	2000	930481 00
EcoHalo 78mm 2y	80W	R7s	230V	1BC	10	1400	2000	920949 00
EcoHalo 78mm 2y	80W	R7s	230V	1BC	10	1400	2000	930504 00
EcoHalo 78mm 2y	80W	R7s	240V	1BC	10	1400	2000	938371 00
EcoHalo 78mm 2y	120W	R7s	230V	1BC	10	2250	2000	920963 00
EcoHalo 78mm 2y	120W	R7s	240V	1BC	10	2250	2000	938395 00

420101022

MV Halogen without Reflector EcoHalo Linear Compact

Additional technical data


Product name	Color Rendering Index (R _a)	Color Temperature (K)	Bulb Finish	Bulb	Energy Efficiency Label (EEL)	Dimmable	Operating Position
EcoHalo 78mm 2y 48W R7s 230V	100	2900	Clear	T4	C	yes	Any
EcoHalo 78mm 2y 80W R7s 230V	100	2900	Clear	T4	C	yes	Any
EcoHalo 78mm 2y 120W R7s 230V	100	2900	Clear	T4	C	yes	Any
EcoHalo 78mm 2y 80W R7s 240V	100	2900	Clear	T4	C	yes	Any
EcoHalo 78mm 2y 120W R7s 240V	100	2900	Clear	T4	C	yes	Any

Logistic data

Product name	Packing type	Packing type description	Packs per outer box	Packing configuration
EcoHalo 78mm 2y 48W R7s 230V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 80W R7s 230V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 120W R7s 230V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 48W R7s 230V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 80W R7s 230V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 80W R7s 240V	1BC	1 Lamp in a Blister Card	10	10
EcoHalo 78mm 2y 120W R7s 240V	1BC	1 Lamp in a Blister Card	10	10

Product name	Quantity per pack	Packing length (mm)	Packing width (mm)	Packing height (mm)	Gross weight per piece (g)	Net weight per piece (g)
EcoHalo 78mm 2y 48W R7s 230V	1	202	155	133	25.8	6
EcoHalo 78mm 2y 80W R7s 230V	1	202	155	133	25.8	6
EcoHalo 78mm 2y 120W R7s 230V	1	202	155	133	25.8	6
EcoHalo 78mm 2y 48W R7s 230V	1	202	155	133	25.8	6
EcoHalo 78mm 2y 80W R7s 230V	1	202	155	133	25.8	6
EcoHalo 78mm 2y 80W R7s 240V	1	202	155	133	26.8	7
EcoHalo 78mm 2y 120W R7s 240V	1	202	155	133	26.8	7

Cap/base



Additional extended technical data

Product name	Lamp Current (A)	Luminous Efficacy Lamp (lm/W)	Bulb Temperature (°C [max.])	Pinch Temperature (°C [max.])
EcoHalo 78mm 2y 48W R7s 230V	0.21	15.6	900	350
EcoHalo 78mm 2y 80W R7s 230V	0.35	17.5	900	350
EcoHalo 78mm 2y 120W R7s 230V	0.52	18.7	900	350
EcoHalo 78mm 2y 80W R7s 240V	0.33	17.5	900	350
EcoHalo 78mm 2y 120W R7s 240V	0.50	18.7	900	350

Burning position

